



現場總綫 M12 連接綫

Fieldbus M12 Cable Assembly



現場總綫 M12 連接綫

Fieldbus M12 Cable Assembly

特點 Features

- 符合現場總綫與工業以太網應用
- TPU 或 PA 工程塑料注塑成型
- 耐油耐彎曲超柔屏蔽電纜，彎曲壽命500萬次
- 採用UL 認證材料，符合 CE 和 RoHS 規範
- Meeting industrial fieldbus and EtherCAT applications
- Durable TPU or PA overmolding for industrial applications
- Flexible oil-resistant shielded cable for 5 million bending cycles
- UL approval materials, CE and RoHS compliant

訂購編號 Ordering Information

XM - FB - MS - A5 - FS - US 3

① ② ③ ④ ⑤ ⑥

① 接口標準 Interface Standard
FB 現場總綫 Fieldbus Series

②、④ 連接器型式 Connector Type
FS 直型母插頭 Female Straight Plug
FR 彎型母插頭 Female Angled Plug
MS 直型公插頭 Male Straight Plug
MR 彎型公插頭 Male Angled Plug
FL 散綫 Flying Leads

③ 芯數 Poles
A4 A Code 4P AS-i, CC-Link, F-F
A5 A Code 5P Devicenet, CANopen
B5 B Code 5P PROFIBUS DP
D4 D Code 4P EtherNet/IP PROFINET
X8 X Code 8P EtherNet/IP PROFINET 10Gbps

⑤ 電纜類型 Cable Type
VS Flexible PVC Cable
US Durable PUR Cable

⑥ 綫長(米) Cable Length(m) **1~20**

