

Camera Link 機器視覺連接綫

Camera Link Cables

特點 Features

- 兼容Camera Link V2.0 標準規範
- TPU 或 PA 工程塑料注塑成型
- 耐油耐彎曲超柔屏蔽電纜，彎曲壽命500萬次
- 採用UL 認證材料，符合 CE 和 RoHS 規範
- Compatible with Camera Link V2.0 standard
- Durable TPU or PA overmolding for industrial applications
- Flexible oil-resistant shielded cable for 5 million bending cycles
- UL approval materials, CE and RoHS compliant

訂購編號 Ordering Information

XMV-CL-M 1-H U-VS 3

① ② ③ ④ ⑤ ⑥ ⑦

① 接口標準 Interface Standard

CL Camera Link
PoCL Power over Camera Link
PoCLL Power over Camera Link-Lite

②、④ 連接器型式 Connector Type

M MDR MALE 26P
H HDR MALE 26P
HS HDR MALE 14P(POCL Lite)

③、⑤ 注塑型式 Overmold Type

1 直型 Straight
U 上彎型 Up Angle
D 下彎型 Down Angle
L 左彎型 Left Angle
R 右彎型 Right Angle
UE 上彎長型 Extended Up Angle
DE 下彎長型 Extended Down Angle
LE 左彎長型 Extended Left Angle
RE 右彎長型 Extended Right Angle

⑥ 電纜類型 Cable Type

VS 超柔電纜 Flexible PVC Cable Black
US 耐彎曲電纜 Durable PUR Cable Green
LS 低煙無鹵電纜 LSZH Cable Black

⑦ 綫長(米) Cable Length(m) 1~10

連接器型式 Connector Type Options



GigE 機器視覺連接綫

GigE Vision Cables

特點 Features

- 兼容GigE V2.0 標準規範
- TPU 或 PA 工程塑料注塑成型
- 耐油耐彎曲超柔 Cat 6a 電纜，彎曲壽命500萬次
- 採用UL 認證材料，符合 CE 和 RoHS 規範
- Compatible with GigE V2.0 standard
- Durable TPU or PA overmolding for industrial applications
- Flexible oil-resistant Cat 6a cable for 5 million bending cycles
- UL approval materials, CE and RoHS compliant

訂購編號 Ordering Information

XMV-GE-H 1-RS U-VS 3

① ② ③ ④ ⑤ ⑥ ⑦

① 接口標準 Interface Standard

GE GigE Vision

②、④ 連接器型式 Connector Type

H 直型插頭 Horizontal RJ45 Plug

HS 直型螺絲插頭 Horizontal RJ45 Plug With Screw

VS 垂直螺絲插頭 Vertical RJ45 Plug With Screw

RS 彎型螺絲插頭 Angled RJ45 Plug With Screw

MX 圓型插頭 M12 X-Code 8P Plug

③、⑤ 注塑型式 Overmold Type ⑥ 電纜類型 Cable Type

1 直型

Straight

U 上彎型

Up Angle

D 下彎型

Down Angle

L 左彎型

Left Angle

R 右彎型

Right Angle

VS 超柔電纜

Flexible Cat 6a PVC Cable Black

US 耐彎曲電纜

Durable Cat 6a PUR Cable Green

LS 低煙無鹵電纜

LSZH Cat 6a Cable Black

⑦ 綫長(米) Cable Length(m) **1~20**

連接器型式 Connector Type Options



Analog 工業相機 連接綫

Analog Camera Cables

特點 Features

- 符合工業相機和工業傳動連接應用
- TPU 或 PA 工程塑料注塑成型
- 耐油耐彎曲超柔屏蔽電纜，彎曲壽命500萬次
- 採用UL 認證材料，符合 CE 和 RoHS 規範
- Meeting industrial camera interface and motion applications
- Durable TPU or PA overmolding for industrial applications
- Flexible oil-resistant shielded cable for 5 million bending cycles
- UL approval materials, CE and RoHS compliant

訂購編號 Ordering Information

XMV-A-12S 1-12P 1-VS 3

① ② ③ ④ ⑤ ⑥ ⑦

① 接口標準 Interface Standard

A Analog

②、④ 連接器型式 Connector Type

12S 12P Female Plug
12SR 12P Female Angled Plug
12P 12P Male Plug
12PR 12P Male Angled Plug
12PJ 12P Male Jack
6S 6P Female Plug
6SR 6P Female Angled Plug
6P 6P Male Plug
6PR 6P Male Angled Plug
FL Flying Leads

③、⑤ 注塑型式 Overmold Type

1 直型 Straight
U 上彎型 Up Angle
D 下彎型 Down Angle
L 左彎型 Left Angle
R 右彎型 Right Angle

⑥ 電纜類型 Cable Type

VS 超柔電纜 Flexible PVC Cable Black
US 耐彎曲電纜 Durable PUR Cable Green
LS 低煙無鹵電纜 LSZH Cable Black

⑦ 綫長(米) Cable Length(m) **1-20**

連接器型式 Connector Type Options

